



DIGIMON

Digital two-way manifold

- 61 refrigerant tables incl R410A, R422D and R744 (CO2)
- Accuracy: Class 1.0
- Pressure range: -0,95 bar to +60 bar
- K-type thermocouple temperature measuring
- K-type Clamp thermocouple (optional)
- Excellent temperature measuring accuracy
- Fast Superheat & Subcool calculation and display
- Simple indicative bar graph display
- Big, illuminated and protected LCD screen
- Updates reading every 3 seconds
- Reset function
- User friendly modified housing
- Fibre glass forced handwheels with REFECO Logo
- Auto shut-off
- Battery level indicator



Versions

Designation	CCL-60	2 x CL-60-1/2"-20UNF	CA-CCL-60	2 x CA-CL-60-1/2"-20UNF	DIGIMON-CLAMP	in cardboard box	in a sturdy plastic case	Part No.
DIGIMON-8						x		4676463
DIGIMON-3	x						x	4676446
DIGIMON-3-PLUS	x	x					x	4676455
DIGIMON-3-PLUS-CLAMP	x	x			x		x	4681483
DIGIMON-3-PLUS-CA			x				x	4679780

Accessories

M2-7-SET-R	Blue handwheel	4677826
M2-7-SET-B	Red handwheel	4677834
DIGIMON-SENSOR-K-TYPE	Thermocouple type K for DIGIMON	4681394
DIGIMON-CLAMP	Clamp thermocouple type K for DIGIMON	4681466
M2-10-95-R/10	Complete valve set with 2 gaskets	4662607
M4-6-04-R/10	Piston including 2 gaskets	4662624
M4-6-11	Assembly of sight glass, 2 gaskets and threads brass ring	4491018
M4-6-11-T	Key for manifold sight glass	4493169
A-32000	Tool for valve core	9880890
DIGIMON-BATTERY-COVER	Battery compartment cover	4676374
DIGIMON-CASE	Carrying Case	4676497